Rack of Labs (RoL)

Share, deploy, test

Ultimate goals

- Share devices in a lab across a team
- Automated test execution on bare metal systems
- Bulk deployment of EVE-OS
- Give trusted partners an access to hardware

Automated test execution on bare metal

- Support both BMC quipped devices and single board computers
- Support for x86, ARM and RISC-V architectures
- Automatic device allocation

Bulk deployment of EVE-OS

- Can be used during manufacturing by OEMs
- No special HW is required
- Plug and Play (no need to babysit the device)

Device sharing

- Share the limited number of devices among team members
 - Reserve
 - Release
 - Notify

Requirements and constraints

- A fleet of devices under test (DUT) is located in a remote lab
- Need a unified solution for
 - Device reservation
 - Grouping a subset of devices into a cluster within the same VLAN
 - Isolating devices in same lab (if some shared with partners)
 - Deployment of OS (EVE, Windows, Linux, etc) onto DUT over iPXE
 - Remote device control

Alternative solution considered -- Tinkerbell

- Tinkerbell is used and supported by Equinix Metal
 - Pros
 - Well known and stable solution for device provisioning
 - Community support
 - Cons
 - BMC support is experimental
 - Deployment only, no device sharing ability
 - No network management
 - No UI

RoL current status

- UI skeleton is ready
 - Device reservation
 - Device provisioning (RPi)
- CLI application is almost ready
- TFTP/DHCP with custom callbacks
- RPi power control using PoE

RoL plans


Short-term

- Run CI/CD on ARM boards
- Automatic VLAN creation


Long-term

- Bulk deployment of EVE-OS
- HW sharing
- Support for BMC and x86 boot scenarios

High level architecture



Topology



Device template

- Describes how the device is controlled
 - IPMI commands
 - iLO or other proprietary REST API calls
- One template can be derived from another. (e.g. RPi-8GB is derived from RPi)
- Boot stages
 - Stages for x86 and single board computers are quite different
 - Files published on TFTP depends on current device state

Teams and projects

- Team is a group of users
- Each team can see all the devices and who reserved them
- Each user can have multiple projects
- Each project is a group of devices
 - Sometimes devices might not be available
- A reserved device owner is notified when the device is requested
 - Reservation owner can either decline or release the device to a new owner

Device reservation

- Two scenarios
 - Manually pick a device from a pool (used for projects)
 - Get a first available device by specified criteria (e.g. Model and RAM size). Used for CI/CD projects

Summary, future work, feedback

- Summary bullets
 - Fills a current void in EVE-OS Arm testing
 - Etc.
- Future work
 - Summarize ideas
 - Any other thoughts
- Your suggestions???